POTENTIOMETRIC SURFACE OF THE CLAYTON AQUIFER IN GEORGIA, OCTOBER 1990

U.S. GEOLOGICAL SURVEY



Prepared in cooperation with

GEORGIA DEPARTMENT OF NATURAL RESOURCES ENVIRONMENTAL PROTECTION DIVISION GEORGIA GEOLOGIC SURVEY

> CITY OF ALBANY WATER, GAS, AND LIGHT COMMISSION

> > Open-File Report 91-208

POTENTIOMETRIC SURFACE OF THE CLAYTON AQUIFER IN GEORGIA, OCTOBER 1990

By Michael F. Peck and Robert J. Allen

U.S. GEOLOGICAL SURVEY

Open-File Report 91-208

Prepared in cooperation with

GEORGIA DEPARTMENT OF NATURAL RESOURCES
ENVIRONMENTAL PROTECTION DIVISION
GEORGIA GEOLOGIC SURVEY

CITY OF ALBANY WATER, GAS, AND LIGHT COMMISSION



Doraville, Georgia

U.S. DEPARTMENT OF THE INTERIOR MANUEL LUJAN, JR., Secretary

U.S. GEOLOGICAL SURVEY

Dallas L. Peck, Director

For additional information write to:

District Chief
U.S. Geological Survey, WRD
6481 Peachtree Industrial Blvd.
Suite B
Doraville, GA 30360

Copies of this report can be purchased from:

U.S. Geological Survey
Books and Open-File Reports
Federal Center, Bldg. 810
Box 25425
Denver, CO 80225

CONTENTS

Abstract 1

References 1

ILLUSTRATION

Figure 1.--Potentiometric surface of the Clayton aquifer in southwestern Georgia, October, 1990 2

CONVERSION FACTOR

Multiply inch-pound unit

by

to obtain metric units

Flow

million gallons per day (Mgal/d)

0.04381

cubic meter per second (m³/s)

VERTICAL DATUM

Sea Level--In this report "sea level" refers to the National Geodetic Vertical Datum of 1929 (NGVD of 1929)--a geodetic datum derived from a general adjustment of the first-order level nets of both the United States and Canada, formerly called "Mean Sea Level of 1929."

POTENTIOMETRIC SURFACE OF THE CLAYTON AQUIFER IN GEORGIA, OCTOBER 1990

By

Michael F. Peck and Robert J. Allen

ABSTRACT

The Clayton aquifer in southwestern Georgia consists of limestone and sand of Paleocene age (Clarke and others, 1984). The aquifer supplies more than 33 million gallons of water per day for agricultural and municipal use (Pierce and Kundel, 1990).

A potentiometric surface shows the level to which water would rise in tightly-cased wells that fully penetrate an aquifer. This report shows the potentiometric surface of the Clayton aquifer in southwestern Georgia.

During October 22-30, 1990, water-level measurements in 79 wells tapping the Clayton aquifer in southwestern Georgia, and stream elevations at 17 sites where the aquifer was under water-table conditions, were used to construct the potentiometric surface of the aquifer for October 1990. The potentiometric surface was mapped using contour lines of equal water-level altitude (fig. 1). The October 1990 potentiometric surface of the Clayton aquifer is representative of the annual low (or near low) water levels that occurred near the end of the irrigation season.

Maps showing the potentiometric surface of the Clayton aquifer in southwestern Georgia are prepared annually by the U.S. Geological Survey, in cooperation with the Georgia Department of Natural Resources, Environmental Protection Division, Georgia Geologic Survey; and the City of Albany, Water, Gas, and Light Commission. These maps are published in an annual report entitled, "Ground-Water Conditions in Georgia, 19XX."

REFERENCES

- Clarke, J.S., Faye, R.E., and Brooks, R., 1984, Hydrogeology of the Clayton aquifer of southwest Georgia: Georgia Geologic Survey Hydrologic Atlas 13, 6 sheets.
- Pierce, R.R., and Kundel, J.E., 1990, Georgia water supply and use; in Carr, J.E., Chase, E.B., Paulson, R.W., and Moody, D.W., ed.; National Water Summary, 1987, Hydrologic events and water supply and use: U.S. Geological Survey Water-Supply Paper 2350, p. 215-222.



EXPLANATION

DATA POINT

- Ground water--Altitude of water level in well
- Surface water--Location where stream and water-table altitudes are coincident. Altitude of stream surface is extrapolated from topographic contour map

Figure 1.--Potentiometric surface of the Clayton aquifer in southwestern Georgia, October 1990.